



# G308 RioExpress – Specifications

<b>RADIO PERFORMANCE:</b>	
Indoor/Urban Range (w/ 2.1 dB dipole antenna)	900MHz, up to 1500' (450m); 2.4GHz, up to 600' (180m)
Outdoor RF line-of-sight Range (w/ 2.1 dB dipole antenna)	900MHz, up to 7 miles (11km); 2.4GHz, up to 3 miles (5km)
Outdoor RF line-of-sight Range (w/ high gain antenna)	900MHz, up to 20 miles (32km); 2.4GHz, up to 10 miles (16km)
Transmit Power Output	900MHz, 100mW; 2.4GHz, 50mW
<b>DATA COMMUNICATIONS:</b>	
Data Rate (Throughput)	9600 baud (bps)
DIP Switch options	<ul style="list-style-type: none"> <li>• 7 RF Net codes (Channels)</li> <li>• 63 Device Address (per Channel)</li> <li>• 4 poll rates (continuous, every second, every 10 seconds, every 60 seconds)</li> </ul>
Master/Slave pair	Self-managed data communications (based on DIP Switch settings)
Modbus Slave	Standard Modbus Slave RTU protocol. Poll from any Modbus Master, using compatible SS Radio Modem (i.e. Model G306-040 Wireless Modem)
Comm. Fail Action	<ul style="list-style-type: none"> <li>• DIP Switch selection for DO Hold/Off, AO Hold/Zero.</li> <li>• Comm Fail turns on DO5 open-collector sink driver (300mA, 30Vdc max load)</li> </ul>
<b>Inputs &amp; Outputs (I/O):</b>	
Digital Inputs (DI)	<ul style="list-style-type: none"> <li>• 4 ea. Digital Inputs (DI 1-4), non-latching, pluggable screw terminals</li> <li>• DI 1-2 are also transition-sensing for totalize/rate or event-capture (not available when used as cable-replacement pair).</li> <li>• Optical coupled for surge and noise tolerance</li> <li>• Active low (power common), non-latching, approx. 4mA wetting current</li> <li>• Power-save mode includes optional DI power-down</li> </ul>
Digital Outputs (DO)	<ul style="list-style-type: none"> <li>• 4 ea. Digital Outputs (DO 1-4), Normally-open (N.O.) dry Relay contacts</li> <li>• Contact rating: 2 Amps 250Vac / 30Vdc General Purpose, Pilot Duty D150</li> <li>• Modbus registers for Latched DOs or Timed DOs (not available with cable-replacement pair).</li> <li>• DIP Switch Selectable "Comm Fail" action on DO 1-4 (Hold current state, or Off)</li> <li>• DO5: Comm Fail turns on DO5 open-collector sink driver (300mA, 30Vdc max load)</li> </ul>
Analog Inputs (AI)	<ul style="list-style-type: none"> <li>• 2 ea. Analog Inputs (AI 1-2), single ended</li> <li>• 0-5Vdc (1-5V) or 0-20mA (4-20mA), DIP Switch selected for each AI</li> <li>• 12 bit resolution. Overall accuracy 0.25% FS. Typical 0.1% at 25 degrees C.</li> <li>• Over-voltage tolerance of +/-30Vdc.</li> <li>• Transducer power (Vx) is on screw terminal with each AI; DIP Switch selected 12V or 24V. Power-save mode includes optional Vx power-down.</li> <li>• Third Analog Input (AI 3) internally monitors power supply voltage; 0-32 Volt range (not available with cable-replacement pair).</li> </ul>
Analog Outputs (AO)	<ul style="list-style-type: none"> <li>• 2 ea. Analog Outputs (AO 1-2), single ended</li> <li>• Both 0-5VDC (1-5Vdc) and 0-20mA (4-20mA) provided. Voltage outputs are recommended for low-power applications.</li> <li>• Overall accuracy 0.45% FS. Typical 0.2% @ 25 degrees C. (1-5V or 4-20mA range)</li> <li>• DIP Switch Selectable "Comm Fail" action on Analog Outputs (Hold current value, or Zero)</li> </ul>
<b>POWER INPUT:</b>	
Input Voltage/ Power	10-30 Vdc, 5 Watts max.
Current, Power-Save (I <sub>PS</sub> )	I <sub>PS</sub> = 7mA @ 12Vdc
Current, Receive/Standby (I <sub>RX</sub> )	I <sub>RX</sub> = 38mA @ 12Vdc
Current, Transmit (I <sub>TX</sub> )	I <sub>TX</sub> = 70mA @ 12Vdc
Actual installed current draw	Actual average current draw varies with Poll Rate and Power-Save settings. Also, Sensor and I/O Current loads add to the overall Supply Current requirements
<b>MISCELLANEOUS:</b>	
Operating Temperature	-40 to 85 degrees C., 5-95% non-condensing humidity
Diagnostics	LEDs: CPU status, RSSI, TX, RX, DIs, DOs and Comm Fail. LED Enable is toggled with Pushbutton, and has a 30 min. timeout.
Data Comm Port 2	4 pin latching header, used for factory testing only.
Surge protection	All power, serial port and I/O connections meet or exceed minimum standards for ESD, EFT, and Surge withstand per the international IEC 1000-4 standards
Certifications	FCC Part 15 Class A; CSA/UL certification for Class I, Div II, Groups A,B,C,D (pending)
<b>PHYSICAL:</b>	
Field Wiring Connections	All wire connections are pluggable screw terminals, 0.2" spacing.
Size & Weight	Dimensions, 6.3" long x 4.15" wide x 1.55" high overall; Weight 11 oz. (300g)
Mounting	Panel mounting, 5.7" x 2.6" rectangular pattern "key-hole", #6 or #8 pan-head screws recommended. Optional clip available for DIN Rail mounting.

G308\_DataSheet\_CABriggs\_2007-06-06

A Product of:

G3 Technologies, Inc.  
2536 W. 239<sup>th</sup> St, Louisburg, KS 66053  
ph 913-947-7205 [www.g3ti.com](http://www.g3ti.com)

For Sales and  
Support, contact:

**C A Briggs Company**  
**The LevelWorks® People**  
E-Mail: [sales@cabriggs.com](mailto:sales@cabriggs.com)  
215-784-9250; Fax: 215-784-0611  
632 Davisville Road  
Willow Grove, PA 19090

© 2007 G3 Technologies, Inc.